



**SPECIFICATIONS**

Voltage rating: 50V AC, DC  
 Current rating: 1.0A AC/DC (AWG#28)  
 Withstanding Voltage: 500V AC/minute  
 Insulation resistance: 100M Ωmin  
 Temperature range: -25 °C - +85°C  
 Contact resistance: 20m Ω

**HOUSING**

Part No: SCT1001H-XX  
 Poles: 2-20  
 Material: PBT+15% Glass Fiber  
 Q'TY: 1000 pcs/bag

PART NO	DIMENSION		PART NO	DIMENSION	
	A	B		A	B
SCT1001H-02	1.00	5.00	SCT1001H-12	11.00	15.00
SCT1001H-03	2.00	6.00	SCT1001H-13	12.00	16.00
SCT1001H-04	3.00	7.00	SCT1001H-14	13.00	17.00
SCT1001H-05	4.00	8.00	SCT1001H-15	14.00	18.00
SCT1001H-06	5.00	9.00	SCT1001H-16	15.00	19.00
SCT1001H-07	6.00	10.00	SCT1001H-17	16.00	20.00
SCT1001H-08	7.00	11.00	SCT1001H-18	17.00	21.00
SCT1001H-09	8.00	12.00	SCT1001H-19	18.00	22.00
SCT1001H-10	9.00	13.00	SCT1001H-20	19.00	23.00
SCT1001H-11	10.00	14.00			

OPERATION	~ 10	±0.15	DRAW	Micky.Liu	2006/05/02	SCALE		森康达电子有限公司 S'CONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	±0.30	CHECK	Judy.Huang	2006/05/02	UNIT	mm		
ANGLE	30 ~	±0.50	APPROVE	Hellen.Li	2006/05/02	SIZE	A4	PART NO.	SCT1001H-XP
DIM	± Z'					SHEET	1/1	TITLE:	SH1.0 HOUSING
TOL						PROJ.		DRAWING NO.	SCT1001

REV	0	05/12/27	NEW	MODIFICATION DESCRIPTION	CHANGE	APPROVE	1	2	3	4	5	6	7	8	9	10
-----	---	----------	-----	--------------------------	--------	---------	---	---	---	---	---	---	---	---	---	----