



**SPECIFICATIONS**

Voltage rating: 50V AC, DC  
 Current rating: 1.0A AC/DC  
 Withstanding Voltage: 500V AC/minute  
 Insulation resistance: 100MΩ min  
 Temperature range: -25 °C - +85°C  
 Contact resistance: 20mΩ max

**TERMINAL**

Part No: SCT1010T  
 Thickness: 0.12mm  
 Material: Phosphor. Bronze, Tin Plated.  
 Wire Range: AWG#28-#32 (OD0.8mm)  
 Reel Q'ty: 20,000 pcs/reel

OPERATION	DRAW	Judy.Huang	2006/05/02	SCALE
~ 10 ±0.15	DESIGN			mm
20 ~ 30 ±0.30	CHECK	Micky.Liu	2006/05/02	A4
30 ~ ±0.50	Angle DIM			1/1
± 2' TOL	APPROVE	Hellen.Li	2006/05/02	PROJ.

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT1010T  
 TITLE: 1.0mm TERMINAL  
 DRAWING NO. SCT1010

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE
0	05/12/27	NEW		

1 2 3 4 5 6 7 8 9 10