


■ SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 1A, AC, DC (AWG#28)
- Withstanding voltage: 500V AC/minute
- Insulation resistance: 100MΩ min
- Temperature range: -40°C - +85°C
- Contact resistance: 20mΩ max

■ HOUSING

- Part No.: SCT1251H-XX
- Poles: 2-16
- Material: Nylon 66 UL94V-0
- Q' TY: 1, 000 pcs/bag



NO	PART NO	DIMENSION (mm)		
		A	B	C
1	SCT1251H-02	1.25	4.25	2.95
2	SCT1251H-03	2.50	5.50	4.20
3	SCT1251H-04	3.75	6.75	5.45
4	SCT1251H-05	5.00	8.00	6.70
5	SCT1251H-06	6.25	9.25	7.95
6	SCT1251H-07	7.50	10.50	9.20
7	SCT1251H-08	8.75	11.75	10.45
8	SCT1251H-09	10.00	13.00	11.70

NO	PART NO	DIMENSION (mm)		
		A	B	C
9	SCT1251H-10	11.25	14.25	12.95
10	SCT1251H-11	12.50	15.50	14.20
11	SCT1251H-12	13.75	16.75	15.45
12	SCT1251H-13	15.00	18.00	16.70
13	SCT1251H-14	16.25	19.25	17.95
14	SCT1251H-15	17.50	20.50	19.20
15	SCT1251H-16	18.75	21.75	20.45

OPERATION		DRAW		SCALE	
~ 10 ±0.15		Micky.Liu		mm	
DESIGN		CHECK		UNIT	
20 ~ 30 ±0.30		Judy.Huang		A4	
30 ~		2006/05/02		SIZE	
Angle ± 2'		2006/05/02		1/1	
DIM TOL		APPROVE		SHEET	
± 2'		Hellen.Li		1/1	
DATE		CHANGE		PROU.	
05/12/27		APPROVE		DRAWING NO.	
NEW		DATE		MX1.25 HOUSING	
MODIFICATION DESCRIPTION		DATE		SCT1251	
1		2		3	
4		5		6	
7		8		9	
10		11		12	

SCONDAR 森康达电子有限公司
SCONDAR ELECTRONIC LIMITED