



SPECIFICATIONS

Voltage rating: 150V AC, DC
 Current rating: 1A, AC, DC (AWG#28)
 Withstanding voltage: 500V AC/minute
 Insulation resistance: 500M Ωmin
 Temperature range: -25 °C - +85°C
 Contact resistance: 30m Ω max

WAFER

Part No.: SCT1252WR-XXP
 Material: Nylon 66, UL94V-0
 Contact: Brass, Tin plated
 Sloder Tabs: Phosphor Bronze, Tin plated

PART NO.	Dimensions	
	A	B
SCT1252WR-02P	1.25	3.75
SCT1252WR-03P	2.50	5.00
SCT1252WR-04P	3.75	6.25
SCT1252WR-05P	5.00	7.50
SCT1252WR-06P	6.25	8.75
SCT1252WR-07P	7.50	10.00
SCT1252WR-08P	8.75	11.25
SCT1252WR-09P	10.00	12.50
SCT1252WR-10P	11.25	13.75
SCT1252WR-11P	12.50	15.00
SCT1252WR-12P	13.75	16.25
SCT1252WR-13P	15.00	17.50
SCT1252WR-14P	16.25	18.75
SCT1252WR-15P	17.50	20.00

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	PART NO.	DRAWING NO.
0	05/12/27	NEW			~ 10 20 ~ 30 30 ~	Judy.Huang	mm	SCT1252WR-XXP	DF13 1.25 90C WAFER
1					± 0.15 ± 0.30 ± 0.50	2006/05/02			SCT1252WR-XXP
					Angle ± 2'	Micky.Liu	A4		
					DIM TOL	Hellen.Li	1/1		
					APPROVE	2006/05/02			

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED