



**SPECIFICATIONS**

Voltage rating: 150V AC, DC  
 Current rating: 1A, AC, DC (AWG#28)  
 Withstanding voltage: 500V AC/minute  
 Insulation resistance: 500M Ω min  
 Temperature range: -25°C - +85°C  
 Contact resistance: 30mΩ max

**WAFER**

Part No.: SCT1252WV-XXP  
 Material: Nylon 66, UL94V-0  
 Contact: Brass, Tin plated  
 Sloder Tabs: Phosphor Bronze, Tin plated

PART NO.	Dimensions	
	A	B
SCT1252WV-02P	1.25	3.75
SCT1252WV-03P	2.50	5.00
SCT1252WV-04P	3.75	6.25
SCT1252WV-05P	5.00	7.50
SCT1252WV-06P	6.25	8.75
SCT1252WV-07P	7.50	10.00
SCT1252WV-08P	8.75	11.25
SCT1252WV-09P	10.00	12.50
SCT1252WV-10P	11.25	13.75
SCT1252WV-11P	12.50	15.00
SCT1252WV-12P	13.75	16.25
SCT1252WV-13P	15.00	17.50
SCT1252WV-14P	16.25	18.75
SCT1252WV-15P	17.50	20.00

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	PART NO.	TITLE:
0	05/12/27	NEW			~ 10 ±0.15 20 ~ 30 ±0.30 30 ~ ±0.50 Angle ± 2'	Judy.Huang	mm	SCT1252WV-XXP	DF13 1.25 180C WAFER
1						Hellen.Li		SCT1252WV-XXP	

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED

1 2 3 4 5 6 7 8 9 10