



**SPECIFICATIONS**

Voltage rating: 150V AC, DC  
 Current rating: 1A, AC, DC (AWG#28)  
 Withstanding voltage: 500V AC/minute  
 Insulation resistance: 500MΩmin  
 Temperature range: -40°C - +85°  
 Contact resistance: 20mΩ max

**HOUSING**

Part No.: SCT1253HA-XXX  
 Poles: 2-30P  
 Material: Nylon 66, UL94V-0  
 Q'TY: 1,000 pcs/bag

PART NO.	Dimensions		
	A	B	C
SCT1253HA-02P	1.25	4.40	2.75
SCT1253HA-03P	2.50	5.65	4.00
SCT1253HA-04P	3.75	6.90	5.25
SCT1253HA-05P	5.00	8.15	6.50
SCT1253HA-06P	6.25	9.40	7.75
SCT1253HA-07P	7.50	10.65	9.00
SCT1253HA-08P	8.75	11.90	10.25
SCT1253HA-09P	10.00	13.15	11.50
SCT1253HA-10P	11.25	14.40	12.75
SCT1253HA-11P	12.50	15.65	14.00
SCT1253HA-12P	13.75	16.90	15.25
SCT1253HA-13P	15.00	18.15	16.50
SCT1253HA-14P	16.25	19.40	17.75
SCT1253HA-15P	17.50	20.65	19.00
SCT1253HA-20P	23.75	26.90	25.25
SCT1253HA-25P	30.00	33.15	31.50
SCT1253HA-30P	36.25	39.40	37.75

OPERATION	~ 10	±0.15	DRAW	YANG	2016.08.27	SCALE	mm	森康达电子有限公司 SCONDAR ELECTRONIC LIMITED
DESIGN	20 ~ 30	±0.30	CHECK	MCKY	2016.08.27	UNIT	A4	
ANGLE	30 ~	±0.50	APPROVE	ALLEN	2016.08.27	SIZE	1/1	PART NO. SCT1253HA-XXX TITLE: DF14 1.25 Housing with lock DRAWING NO. SCT1253
TOL.	± 2'		PROJ.					

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	5	6	7	8	9	10
0	05/12/27	NEW								