



PART NO	DIMENSION			
	A	B	C	D
SCT1258H-02	1.25	2.20	3.75	--
SCT1258H-03	2.50	3.20	5.00	--
SCT1258H-04	3.75	4.25	6.25	--
SCT1258H-05	5.00	4.25	7.50	--
SCT1258H-06	6.25	6.25	8.75	--
SCT1258H-07	7.50	6.25	10.00	--
SCT1258H-08	8.75	6.25	11.25	8.75
SCT1258H-09	10.00	6.25	12.50	10.00
SCT1258H-10	11.25	8.20	13.75	11.25
SCT1258H-11	12.50	8.20	15.00	12.50
SCT1258H-12	13.75	8.20	16.25	13.75
SCT1258H-13	15.00	8.20	17.50	15.00
SCT1258H-14	16.25	8.20	18.75	16.25
SCT1258H-15	17.50	8.20	20.00	17.50

**SPECIFICATIONS**  
Voltage rating: 150V AC, DC  
Current rating: 1A, AC, DC (AMG#28)  
Withstanding voltage: 500V AC/minute  
Insulation resistance: 100MΩ min  
Temperature range: -40°C - +85°C  
Contact resistance: 20mΩ max

**HOUSING**  
Part No.: SCT1258H-XX  
Poles: 2-15  
Material: Nylon 66 UL94V-0  
Q'TY: 1,000 pcs/bag

OPERATION	~ 10° ±0.15	DRAW	Judy.Huang	2014/09/23	SCALE	mm	 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED
DESIGN	20° ~ 30° ±0.30	CHECK	Micky.Liu	2014/09/23	A4	PART NO.	
ANGLE	30° ~ ±0.50	APPROVE	Hellen.Li	2014/09/23	1/1	TITLE:	
DATE	05/12/27	CHANGE			PROU.	DRAWING NO.	
REV	0	MODIFICATION DESCRIPTION	NEW				