



SPECIFICATIONS

Voltage rating: 100V AC, DC
 Current rating: 1A, AC, DC (AWG#26)
 Withstanding Voltage: 500V AC/minute
 Insulation resistance: 500M Ω /min
 Temperature range: -25°C - +85°C
 Contact resistance: 20m Ω max

HOUSING

Part No: SCT1501H-XXP
 Poles: 02-16
 Material: Nylon 66, UL94V-0
 Q'TY: 1000 pcs/bag

PART NO	DIMENSION	
	A	B
SCT1501H-02	1.50	4.50
SCT1501H-03	3.00	6.00
SCT1501H-04	4.50	7.50
SCT1501H-05	6.00	9.00
SCT1501H-06	7.50	10.50
SCT1501H-07	9.00	12.00
SCT1501H-08	10.50	13.50
SCT1501H-09	12.00	15.00
SCT1501H-10	13.50	16.50
SCT1501H-11	15.00	18.00
SCT1501H-12	16.50	19.50
SCT1501H-13	18.00	21.00
SCT1501H-14	19.50	22.50
SCT1501H-15	21.00	24.00
SCT1501H-16	22.50	25.50

OPERATION	DRAW	Judy.Huang	2006/05/02	SCALE
~ 10 ±0.15	DESIGN			mm
20 ~ 30 ±0.30	CHECK	Micky.Liu	2006/05/02	A4
30 ~ Angle DIM	CHECK	Micky.Liu	2006/05/02	1/1
± 2 TOL	APPROVE	Hellen.Li	2006/05/02	PROU.

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE
0	05/12/27	NEW		

