



SPECIFICATIONS
 Voltage Rating: 100V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT2001WV-XXPB
 Poles: 2-16
 Material: Nylon 66, UL94V-2
 Contact: Brass, Tin plated

PART NO	DIMENSION	
	A	B
SCT2001WV-02PB	2.00	6.00
SCT2001WV-03PB	4.00	8.00
SCT2001WV-04PB	6.00	10.00
SCT2001WV-05PB	8.00	12.00
SCT2001WV-06PB	10.00	14.00
SCT2001WV-07PB	12.00	16.00
SCT2001WV-08PB	14.00	18.00
SCT2001WV-09PB	16.00	20.00
SCT2001WV-10PB	18.00	22.00
SCT2001WV-11PB	20.00	24.00
SCT2001WV-12PB	22.00	26.00
SCT2001WV-13PB	24.00	28.00
SCT2001WV-14PB	26.00	30.00
SCT2001WV-15PB	28.00	32.00
SCT2001WV-16PB	30.00	34.00

OPERATION	~ 10	±0.15	DRAW	Judy Huang	2006/05/02	SCALE	mm
DESIGN	20 ~ 30	±0.30	CHECK	Micky Liu	2006/05/02	UNIT	A4
ANGLE	30 ~	±0.50	APPROVE	Hellen.Li	2006/05/02	SIZE	1/1
DIM	± 2'					SHEET	1/1
TOL						PROJ.	

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT2001WV-XXPB
 TITLE: PH2.0 180C WAFER

DRAWING NO. SCT2001

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE
0	05/12/27	NEW		