



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING

Part No: SCT2004H-2xXXP
 Poles: 2x2-17
 Material: Nylon 66, UL94V-2

| PART NO. | Dimensions | |
|----------------|------------|-------|
| | B | A |
| SCT2004H-2X2P | 6.00 | 2.00 |
| SCT2004H-2X3P | 8.00 | 4.00 |
| SCT2004H-2X4P | 10.00 | 6.00 |
| SCT2004H-2X5P | 12.00 | 8.00 |
| SCT2004H-2X6P | 14.00 | 10.00 |
| SCT2004H-2X7P | 16.00 | 12.00 |
| SCT2004H-2X8P | 18.00 | 14.00 |
| SCT2004H-2X9P | 20.00 | 16.00 |
| SCT2004H-2X10P | 22.00 | 18.00 |
| SCT2004H-2X11P | 24.00 | 20.00 |
| SCT2004H-2X12P | 26.00 | 22.00 |
| SCT2004H-2X13P | 28.00 | 24.00 |
| SCT2004H-2X14P | 30.00 | 26.00 |
| SCT2004H-2X15P | 32.00 | 28.00 |
| SCT2004H-2X16P | 34.00 | 30.00 |
| SCT2004H-2X17P | 36.00 | 32.00 |

| | | | | | | | | |
|-----------|----------|--------------------------|---------|------------|------------|-------------|---------|---|
| OPERATION | ~ 10 | ±0.15 | DRAW | Judy Huang | 2006/05/02 | SCALE | mm | 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED |
| DESIGN | 20 ~ 30 | ±0.30 | CHECK | Micky Liu | 2006/05/02 | UNIT | A4 | |
| Angle | 30 ~ | ±0.50 | APPROVE | Hellen Li | 2006/05/02 | SHEET | 1/1 | |
| REV | DATE | MODIFICATION DESCRIPTION | CHANGE | APPROVE | PROJ. | DRAWING NO. | SCT2004 | |
| 0 | 05/12/27 | NEW | | | | | | |