


A-A



B-B

SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT2004T
 Wire Range: AWG#24-#28 (OD1.5mm)
 Material: Phos. Bronze
 Finish: Tin Plated
 Thickness: 0.2mm
 QTY: 10,000PCS/Reel

OPERATION		DRAW		SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
~ 10	±0.15	DESIGN	Judy.Huang	UNIT	mm		
20 ~ 30	±0.30	CHECK	Micky.Liu	SIZE	A4	PART NO.	SCT2004T
30 ~	±0.50	APPROVE	Hellen.Li	SHEET	1/1	TITLE:	PHD2.0 TERMINAL
Angle	± 2'	CHANGE	2006/05/02	PROJ.		DRAWING NO.	SCT2004T
DIM	TOL	APPROVE					
REV	DATE	MODIFICATION DESCRIPTION					
0	05/12/27	NEW					
1							