



NOTES:

PART NO. : SCT2004WR-2XNP
 Current Rating: 2A AC, DC
 Voltage Rating: 250V AC, DC
 Temperature Range: -25° C +85° C
 Contact Resistance: 20m max
 Insulation Resistance: 1000M min
 Withstanding Voltage: 800V AC/minute
 Material: PA66 UL 94V-0

PART NO.	Dimensions	
	A	B
SCT2004-WR-2X3PB	8.00	4.00
SCT2004-WR-2X4PB	10.00	6.00
SCT2004-WR-2X5PB	12.00	8.00
SCT2004-WR-2X6PB	14.00	10.00
SCT2004-WR-2X7PB	16.00	12.00
SCT2004-WR-2X8PB	18.00	14.00
SCT2004-WR-2X9PB	20.00	16.00
SCT2004-WR-2X10PB	22.00	18.00
SCT2004-WR-2X11PB	24.00	20.00
SCT2004-WR-2X12PB	26.00	22.00
SCT2004-WR-2X13PB	28.00	24.00
SCT2004-WR-2X14PB	30.00	26.00
SCT2004-WR-2X15PB	32.00	28.00
SCT2004-WR-2X16PB	34.00	30.00
SCT2004-WR-2X17PB	36.00	32.00

REV	DATE	MODIFICATION DESCRIPTION	CHANGE APPROVE	OPERATION	DRAW	SCALE	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW		~ 10 20 ~ 30 30 ~	DESIGN CHECK	mm A4	SCT2004WR-2XXXPB	PHD2.0 90C WAFER	SCT2004WR
1				Angle DIM	CHECK APPROVE	1/1			

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED