



NOTES:

PART NO. : SCT2004WV-2\*NPB  
 Current Rating: 2A AC, DC  
 Voltage Rating: 250V AC, DC  
 Temperature Range:  $-25^{\circ}\text{C}$  ~  $+85^{\circ}\text{C}$   
 Contact Resistance:  $20\text{m}\ \Omega_{\text{max}}$   
 Insulation Resistance:  $\square 1000\text{M}$  min  
 Withstanding Voltage: 800V AC/minute  
 Material: Pa66 UL 94V-2

PART NO.	Dimensions	
	A	B
SCT2004-WV-2X2PB	6.00	2.00
SCT2004-WV-2X3PB	8.00	4.00
SCT2004-WV-2X4PB	10.00	6.00
SCT2004-WV-2X5PB	12.00	8.00
SCT2004-WV-2X6PB	14.00	10.00
SCT2004-WV-2X7PB	16.00	12.00
SCT2004-WV-2X8PB	18.00	14.00
SCT2004-WV-2X9PB	20.00	16.00
SCT2004-WV-2X10PB	22.00	18.00
SCT2004-WV-2X11PB	24.00	20.00
SCT2004-WV-2X12PB	26.00	22.00
SCT2004-WV-2X13PB	28.00	24.00
SCT2004-WV-2X14PB	30.00	26.00
SCT2004-WV-2X15PB	32.00	28.00
SCT2004-WV-2X16PB	34.00	30.00
SCT2004-WV-2X17PB	36.00	32.00

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE
0	05/12/27	NEW			~ 10 20 ~ 30 30 ~	DESIGN CHECK	mm A4
					Angle DIM	CHECK APPROVE	SHEET 1/1
					$\pm 2$ TOL		TITLE: PHD2.0 180C WF
							DRAWING NO. SCT2004WV

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED