



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING

Part No: SCT2005H-XXP
 Poles: 2-15
 Material: Nylon 66, UL94V-0

PART NO.	Dimensions	
	A	B
SCT2005H-2P	2.00	5.60
SCT2005H-3P	4.00	7.60
SCT2005H-4P	6.00	9.60
SCT2005H-5P	8.00	11.60
SCT2005H-6P	10.00	13.60
SCT2005H-7P	12.00	15.60
SCT2005H-8P	14.00	17.60
SCT2005H-9P	16.00	19.60
SCT2005H-10P	18.00	21.60
SCT2005H-11P	20.00	23.60
SCT2005H-12P	22.00	25.60
SCT2005H-13P	24.00	27.60
SCT2005H-14P	26.00	29.60
SCT2005H-15P	28.00	31.60

OPERATION	~ 10	± 0.15	DRAW	Judy Huang	2006/05/02	SCALE	mm	 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	± 0.30	CHECK	Micky Liu	2006/05/02	UNIT	A4		
Angle	30 ~	± 0.50	APPROVE	Hellen Li	2006/05/02	SIZE	1/1		
DM	± 2					SHEET	1/1	PART NO.	SCT2005H-XXP
DATE	05/12/27		CHANGE			PROJ.		TITLE:	JAE2.0 HOUSING
REV	0		DESCRIPTION	NEW		DRAWING NO.			SCT2005H