



Recommended P.C.B Layout(Top Side)
(Tolerance=±0.05)

SPECIFICATIONS

Voltage Rating: 100V AC/DC
 Current Rating: 1A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2005WV-XXP
 Poles: 2-16
 Material: PA 66, UL94V-0

PART NO	DIMENSION	
	A	B
SCT2005WV-02	2.00	6.00
SCT2005WV-03	4.00	8.00
SCT2005WV-04	6.00	10.00
SCT2005WV-05	8.00	12.00
SCT2005WV-06	10.00	14.00
SCT2005WV-07	12.00	16.00
SCT2005WV-08	14.00	18.00
SCT2005WV-09	16.00	20.00
SCT2005WV-10	18.00	22.00
SCT2005WV-11	20.00	24.00
SCT2005WV-12	22.00	26.00
SCT2005WV-13	24.00	28.00
SCT2005WV-14	26.00	30.00
SCT2005WV-15	28.00	32.00
SCT2005WV-16	30.00	34.00

OPERATION	DRAW	YANG	2015.12.08	SCALE	SCONDAR 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
~ 10 ±0.15	DESIGN			UNIT	mm	
20 ~ 30 ±0.30	CHECK	Micky.Liu	2015.12.08	SIZE	A4	
30 ~ ±0.50	APPROVE	Allen	2015.12.08	SHEET	1/1	
Angle DIM				PROJ.	DRAWING NO. SCT2005WV	
± 2'					TITLE: JAE2.0 180C WAFER	
MODIFICATION DESCRIPTION	CHANGE	APPROVE			SCT2005WV	
NEW						
DATE						
05/12/27						
REV						
0						

SCONDAR 森康达电子有限公司
SCONDAR ELECTRONIC LIMITED