



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER

Part No: SCT2011W-S-F-2XXXXP
 Poles: 2x2-20
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions		
	A	B	C
SCT2011W-S-F-2X02P	2.00	8.50	4.00
SCT2011W-S-F-2X03P	4.00	10.50	6.00
SCT2011W-S-F-2X04P	6.00	12.50	8.00
SCT2011W-S-F-2X05P	8.00	14.50	10.00
SCT2011W-S-F-2X06P	10.00	16.50	12.00
SCT2011W-S-F-2X07P	12.00	18.50	14.00
SCT2011W-S-F-2X08P	14.00	20.50	16.00
SCT2011W-S-F-2X09P	16.00	22.50	18.00
SCT2011W-S-F-2X10P	18.00	24.50	20.00
SCT2011W-S-F-2X11P	20.00	26.50	22.00
SCT2011W-S-F-2X12P	22.00	28.50	24.00
SCT2011W-S-F-2X13P	24.00	30.50	26.00
SCT2011W-S-F-2X14P	26.00	32.50	28.00
SCT2011W-S-F-2X15P	28.00	34.50	30.00
SCT2011W-S-F-2X16P	30.00	36.50	32.00
SCT2011W-S-F-2X20P	38.00	44.50	40.00

OPERATION		DRAW		SCALE	
~ 10	±0.15	JUDY		mm	
20 ~ 30	±0.30	DESIGN		UNIT	
30 ~	±0.50	CHECK	MICKY	SIZE	A4
Angle	± 2'	APPROVE	HELLEN	SHEET	1/1
DIM	TOL	APPROVE	2006.05.09	PROJ.	◆
MODIFICATION DESCRIPTION		CHANGE APPROVE		DRAWING NO.	
0	05/12/27	NEW		DF11 2.0 180C SMT Wafer	
1				SCT2011	

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED