



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2015H-XXP
 Poles: 1-25
 Material: PBT

PART NO.	Dimensions	
	A	B
SCT2015H-01P	2.30	2.30
SCT2015H-02P	2.00	4.30
SCT2015H-03P	4.00	6.30
SCT2015H-04P	6.00	8.30
SCT2015H-05P	8.00	10.30
SCT2015H-06P	10.00	12.30
!	!	!
!	!	!
SCT2015H-20P	38.00	40.30
SCT2015H-21P	40.00	42.30
SCT2015H-22P	42.00	44.30
SCT2015H-23P	44.00	46.30
SCT2015H-24P	46.00	48.30
SCT2015H-25P	48.00	50.30

OPERATION	~ 10	±0.15	DRAW	JUDY	2006.05.09	SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2006.05.09	UNIT	mm		
ANGLE	30 ~	±0.50	APPROVE	HELLEN	2006.05.09	SIZE	A4	PART NO.	SCT2015H-XXP
DIM	± 2'					SHEET	1/1	TITLE:	Dupont 2.0 Housing
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE		PROU.		DRAWING NO.	SCT2015
0	05/12/27	NEW							

1 2 3 4 5 6 7 8 9 10