



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2502H-XXP
 Poles: 2-16
 Material: Nylon 66, UL94V-2

PART NO	DIMENSION	
	A	B
SCT2502H-02	2.50	7.50
SCT2502H-03	5.00	10.00
SCT2502H-04	7.50	12.50
SCT2502H-05	10.00	15.00
SCT2502H-06	12.50	17.50
SCT2502H-07	15.00	20.00
SCT2502H-08	17.50	22.50
SCT2502H-09	20.00	25.00
SCT2502H-10	22.50	27.50
SCT2502H-11	25.00	30.00
SCT2502H-12	27.50	32.50
SCT2502H-13	30.00	35.00
SCT2502H-14	32.50	37.50
SCT2502H-15	35.00	40.00
SCT2502H-16	37.50	42.50

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	CHECK	DATE	SCALE
0	05/12/27	NEW			~ 10 ±0.15	DESIGN		05/12/27	mm
					20 ~ 30 ±0.30	CHECK	MICKY	05/12/28	A4
					30 ~ Angle ± 2'	APPROVE	HELLEN	05/12/28	1/1
					DIM TOL				PROJ.

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT2502H-XXP
 TITLE: XA2.5 HOUSING
 DRAWING NO. SCT2502