



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT2503T
 Wire Range: AWG#22-#28 (OD1.9mm)
 Material: Brass
 Finish: Tin Plated
 Thickness: 0.2mm
 QTY: 8,000PCS/Reel

G 1 2 3 4 5 6 7 8 9 10

OPERATION	~ 10	±0.15	DRAW	CHENA	05/12/27	SCALE	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	05/12/28	UNIT	mm
Angle	30 ~	±0.50	APPROVE	HELLEN	05/12/28	SIZE	A4
DIM	± 2'					SHEET	1/1
TOL						PROJ.	◆
CHANGE	APPROVE					DRAWING NO.	SCT2503
MODIFICATION DESCRIPTION	NEW					PART NO.	SCT2503T
DATE	05/12/27					TITLE:	Dupont2.5 TERMINAL
REV	0					DRAWING NO.	SCT2503

SCT 森康达电子有限公司
 S'CONDAR ELECTRONIC LIMITED

1 2 3 4 5 6 7 8 9 10