



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2511H-XXP
 Poles: 2-15
 Material: Nylon 66, UL94V-0

PART NO.	Dimensions	
	A	B
SCT2511H-02P	2.50	7.00
SCT2511H-03P	5.00	9.50
SCT2511H-04P	7.50	12.00
SCT2511H-05P	10.00	14.50
SCT2511H-06P	12.50	17.00
SCT2511H-07P	15.00	19.50
SCT2511H-08P	17.50	22.00
SCT2511H-09P	20.00	24.50
SCT2511H-10P	22.50	27.00
SCT2511H-11P	25.00	29.50
SCT2511H-12P	27.50	32.00
SCT2511H-13P	30.00	34.50
SCT2511H-14P	32.50	37.00
SCT2511H-15P	35.00	39.50

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	CHECK	SCALE	UNIT	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW			~ 10 ±0.15	DESIGN	MICKY	A4	mm	SCT2511H-XXP	EH2.5 Housing	SCT2511
					20 ~ 30 ±0.30	CHECK	HELLEN	1/1				
					30 ~ ±0.50	APPROVE						
					Angle ± 2'							
					DIM TOL							

森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED