



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2513H-XXP
 Poles: 2-16
 Material: Nylon 66, UL94V-0

PART NO.	Dimensions	
	A	B
SCT2513H-02P	2.50	5.80
SCT2513H-03P	5.00	8.30
SCT2513H-04P	7.50	10.80
SCT2513H-05P	10.00	13.30
SCT2513H-06P	12.50	15.80
SCT2513H-07P	15.00	18.30
SCT2513H-08P	17.50	20.80
SCT2513H-09P	20.00	23.30
SCT2513H-10P	22.50	25.80
SCT2513H-11P	25.00	28.30
SCT2513H-12P	27.50	30.80
SCT2513H-13P	30.00	33.30
SCT2513H-14P	32.50	35.80
SCT2513H-15P	35.00	38.30
SCT2513H-16P	37.50	40.80

OPERATION	~ 10	± 0.15	DRAW	CHENA	2010.12.03	SCALE	森康达电子有限公司 SCONDAR ELECTRONIC LIMITED		
DESIGN	20 ~ 30	± 0.30	CHECK	MICKY	2010.12.03	UNIT	mm		
CHEK	30 ~	± 0.50	APPROVE	HELLEN	2010.12.03	SIZE	A4	PART NO.	SCT2513H-XXP
ANGLE	± 2'					SHEET	1/1	TITLE:	MOLEX2.5 HOUSING
DIM						PROJ.		DRAWING NO.	SCT2513
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE					
0	05/12/27	NEW							