



**SPECIFICATIONS**  
 Voltage Rating: 250V AC/DC  
 Current Rating: 3A AC/DC  
 Withstanding Voltage: 1000V AC/minute  
 Insulation Resistance: 1,000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**TERMINAL**  
 Part No: SCT2513TP  
 Wire Range: AWG#22-#28 (OD1.9mm)  
 Material: Phos. Bronze  
 Finish: Tin Plated  
 Thickness: 0.2mm  
 Q'TY: 10,000PCS/Reel1

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED

OPERATION		~ 10	±0.15	DRAW		CHENA	2010.12.03	SCALE	SCONDAR 森康达电子有限公司	
DESIGN		20 ~ 30	±0.30	CHECK		MICKY	2010.12.03	UNIT	SCONDAR ELECTRONIC LIMITED	
ANGLE		30 ~	±0.50	APPROVE		HELLEN	2010.12.03	SIZE	SCT2513TP	
DIM		± 2'		APPROVE				SHEET	MOLEX2.5 Terminal	
TOL				APPROVE				PROJ.	SCT2513	
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	APPROVE			DRAWING NO.		
0	05/12/27	NEW								