



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT2513WV-XXP
 Poles: 2-16
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions	
	A	B
SCT2513WV-02P	2.50	7.50
SCT2513WV-03P	5.00	10.00
SCT2513WV-04P	7.50	12.50
SCT2513WV-05P	10.00	15.00
SCT2513WV-06P	12.50	17.50
SCT2513WV-07P	15.00	20.00
SCT2513WV-08P	17.50	22.50
SCT2513WV-09P	20.00	25.00
SCT2513WV-10P	22.50	27.50
SCT2513WV-11P	25.00	30.00
SCT2513WV-12P	27.50	32.50
SCT2513WV-13P	30.00	35.00
SCT2513WV-14P	32.50	37.50
SCT2513WV-15P	35.00	40.00
SCT2513WV-16P	37.50	42.50

OPERATION	~ 10	± 0.15	DRAW	CHENA	2010.12.03	SCALE	
DESIGN	20 ~ 30	± 0.30	CHECK	MICKY	2010.12.03	UNIT	mm
CHECK	30 ~	± 0.50	APPROVE	HELLEN	2010.12.03	SIZE	A4
ANGLE	30 ~	± 2'				SHEET	1/1
DIM						PROU.	
DATE	05/12/27		MODIFICATION DESCRIPTION	NEW		PART NO.	SCT2513WV-XXP
REV	0		CHANGE			TITLE:	MOLEX2.5 180C WAFER
			APPROVE			DRAWING NO.	SCT2513

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED