



**SPECIFICATIONS**

Voltage Rating: 250V AC/DC  
 Current Rating: 3A AC/DC  
 Withstanding Voltage: 1000V AC/minute  
 Insulation Resistance: 1000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**HOUSING**  
 Part No: SCT2543H-2xXXP  
 Poles: 2x2-40  
 Material: PBT

PART NO.	Dimensions	
	A	B
SCT2543H-2x02P	2.54	5.08
SCT2543H-2x03P	5.08	7.62
SCT2543H-2x04P	7.62	10.16
SCT2543H-2x05P	10.16	12.70
SCT2543H-2x39P	96.52	99.06
SCT2543H-2x40P	99.06	101.60

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	PART NO.
0	05/12/27	NEW			~ 10 ±0.15	Judy.Huang	mm	SCT2543H-2xXXP
					20 ~ 30 ±0.30	Micky.Liu	A4	DUPont2.54 HOUSING
					30 ~ Angle ± 2'	Hellen.Li	1/1	SCT2543H

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED