



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 100MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2543H-XXP
 Poles: 1-40
 Material: PBT

PART NO.	Dimensions	
	A	B
SCT2543H-01P	---	2.54
SCT2543H-02P	2.54	5.08
SCT2543H-03P	5.08	7.62
SCT2543H-04P	7.62	10.16
SCT2543H-05P	10.16	12.70
SCT2543H-39P	96.52	99.06
SCT2543H-40P	99.06	101.60

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	PART NO.	DRAWING NO.
0	05/12/27	NEW			~ 10 ±0.15 20 ~ 30 ±0.30 30 ~ ±0.50 Angle ± 2'	DESIGN CHECK	UNIT mm SIZE A4 SHEET 1/1	SCT2543H-XXP	DUPONT2.54 HOUSING
						APPROVE	PROU.		SCT2543H

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED