



TYPE	High	Short
<C>	2.92	1.42

**SPECIFICATIONS**  
 Voltage Rating: 250V AC/DC  
 Current Rating: 3A AC/DC  
 Withstanding Voltage: 1000V AC/minute  
 Insulation Resistance: 1000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**HOUSING**  
 Part No: SCT2543HN-2xXXP  
 Poles: 2x2-40  
 Material: PBT

PART NO.	Dimensions	
	A	B
SCT2543HN-2x02P	2.54	5.08
SCT2543HN-2x03P	5.08	7.62
SCT2543HN-2x04P	7.62	10.16
SCT2543HN-2x05P	10.16	12.70
SCT2543HN-2x39P	96.52	99.06
SCT2543HN-2x40P	99.06	101.60

OPERATION	~ 10	±0.15	DRAW	Judy Huang	2006/05/02	SCALE	mm
DESIGN	20 ~ 30	±0.30	CHECK	Micky Liu	2006/05/02	UNIT	A4
ANGLE	30 ~	±0.50	APPROVE	Hellen Li	2006/05/02	SHEET	1/1
DIM	± 2'		PROJ.			DRAWING NO.	SCT2543HN
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE			
0	05/12/27	NEW					
1							

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT2543HN-2xXXP  
 TITLE: Dupont2.54 HOUSING