



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL
 Part No: SCT2543MT
 Wire Range: AWG#24-#26 (OD1. 55mm)
 Material: Brass
 Finish: Tin Plated
 Thickness: 0.20mm
 Q'TY: 10, 000PCS/Reel

REV	DATE	MODIFICATION DESCRIPTION	CHANGE APPROVE	OPERATION	DRAW	SCALE	PART NO.
0	05/12/27	NEW		~ 10 ±0.25	Judy.Huang	mm	SCT2543MT
				20 ~ 30 ±0.30			森康达电子有限公司 SCONDAR ELECTRONIC LIMITED
				30 ~ ±0.50	Micky.Liu	A4	Dupont2.54 MALE TERMINAL
				Angle DIM	2006/05/02	1/1	
				± 2' TOL	Hellen.Li	PROJ.	SCT2543MT
					2006/05/02		

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

1 2 3 4 5 6 7 8 9 10