



**SPECIFICATIONS**  
 Voltage Rating: 250V AC/DC  
 Current Rating: 3A AC/DC  
 Withstanding Voltage: 1000V AC/minute  
 Insulation Resistance: 1000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**TERMINAL**  
 Part No: SCT2543T  
 Wire Range: AWG#24-#26 (OD1.55mm)  
 Material: Brass  
 Finish: Tin Plated  
 Thickness: 0.20mm  
 QTY: 10,000PCS/Reel

REV		DATE		MODIFICATION DESCRIPTION		CHANGE APPROVE		OPERATION		DRAW		SCALE		PART NO.		TITLE:		DRAWING NO.	
0		05/12/27		NEW				~ 10 ±0.25		Judy.Huang		mm		SCT2543T		森康达电子有限公司		SCT2543T	
								20 ~ 30 ±0.30				A4		Dupont12.54		TERMIANL			
								30 ~ ±0.50		CHECK		SHEET		1/1					
								Angle DIM		APPROVE		PROJ.		◆					
								± 2' TOL		Hellen.Li									
										2006/05/02									
										2006/05/02									
										2006/05/02									

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED