



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2544FH-XXP
 Poles: 2-15
 Material: Nylon 66, UL94V-0

PART NO.	Dimensions	
	A	B
SCT2544FH-02P	2.54	7.11
SCT2544FH-03P	5.08	9.65
SCT2544FH-04P	7.62	12.19
SCT2544FH-05P	10.16	14.73
SCT2544FH-06P	12.70	17.27
SCT2544FH-07P	15.24	19.81
SCT2544FH-08P	17.78	22.35
SCT2544FH-09P	20.32	24.89
SCT2544FH-10P	22.86	27.43
SCT2544FH-11P	25.40	29.97
SCT2544FH-12P	27.94	32.51
SCT2544FH-13P	30.48	35.05
SCT2544FH-14P	33.02	37.59
SCT2544FH-15P	35.56	40.13

OPERATION	~ 10 ±0.15	DRAW	YANG	2016.04.30	SCALE		
	20 ~ 30 ±0.30	DESIGN			UNIT	mm	
	30 ~ ±0.50	CHECK	Micky.Liu	2016.04.30	SIZE	A4	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	APPROVE	ALL	PROJ.
0	05/12/27	NEW					
1							

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT2544FH-XXP
 TITLE: MX2.54 CD-ROW FEMALE HOUSING
 DRAWING NO. SCT2544