



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2544HA-XXPB
 Poles: 2-20
 Material: PA66, UL94V-2

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
SCT2544HA-02PB	2.54	5.08	SCT2544HA-13PB	30.48	33.02
SCT2544HA-03PB	5.08	7.62	SCT2544HA-14PB	33.02	35.56
SCT2544HA-04PB	7.62	10.16	SCT2544HA-15PB	35.56	38.10
SCT2544HA-05PB	10.16	12.70	SCT2544HA-16PB	38.10	40.64
SCT2544HA-06PB	12.70	15.24	SCT2544HA-17PB	40.64	43.18
SCT2544HA-07PB	15.24	17.78	SCT2544HA-18PB	43.18	45.72
SCT2544HA-08PB	17.78	20.32	SCT2544HA-19PB	45.72	48.26
SCT2544HA-09PB	20.32	22.86	SCT2544HA-20PB	48.26	50.80
SCT2544HA-10PB	22.86	25.40			
SCT2544HA-11PB	25.40	27.94			
SCT2544HA-12PB	27.94	30.48			

OPERATION	DRAW	CHENA	SCALE	SCONDAR 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
~ 10 ±0.15	DESIGN		mm	PART NO.	SCT2544HA-XPB
20 ~ 30 ±0.30	CHECK	MICKY	SIZE	TITLE:	MX2.54 CD-ROM HOUSING
30 ~ ±0.50	APPROVE	HELLEN	SHEET	DRAWING NO.	SCT2544HA
Angle ± 2'			PROJ.		
DIM TOL					

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE
0	05/12/27	NEW		