



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 5A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING

Part No: SCT3001FH-2XXXP
 Poles: 2-12
 Material: Nylon 66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT3001FH-2X01P	---	3.85
SCT3001FH-2X02P	3.00	6.85
SCT3001FH-2X03P	6.00	9.85
SCT3001FH-2X04P	9.00	12.85
SCT3001FH-2X05P	12.00	15.85
SCT3001FH-2X06P	15.00	18.85
SCT3001FH-2X07P	18.00	21.85
SCT3001FH-2X08P	21.00	24.85
SCT3001FH-2X09P	24.00	27.85
SCT3001FH-2X10P	27.00	30.85
SCT3001FH-2X11P	30.00	33.85
SCT3001FH-2X12P	33.00	36.85

REV	DATE	MODIFICATION DESCRIPTION	CHANGE APPROVE	OPERATION	DRAW	JUDY	SCALE	UNIT	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW		~ 10 ±0.15 20 ~ 30 ±0.30 30 ~ ±0.50 Angle ± 2' DIM TOL	DESIGN		A4	mm	SCT3001FH-2XXXP	MOLEX3.0 FEMALE HOUSING	SCT3001
					CHECK	MICKY					
					APPROVE	HELLEN					
					APPROVE						

SCONBAR 森康达电子有限公司
 SCONBAR ELECTRONIC LIMITED