



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 5A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING

Part No: SCT3001FH-XXP
 Poles: 2-12
 Material: Nylon 66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT3001FH-2P	3.00	6.85
SCT3001FH-3P	6.00	9.85
SCT3001FH-4P	9.00	12.85
SCT3001FH-5P	12.00	15.85
SCT3001FH-6P	15.00	18.85
SCT3001FH-7P	18.00	21.85
SCT3001FH-8P	21.00	24.85
SCT3001FH-9P	24.00	27.85
SCT3001FH-10P	27.00	30.85
SCT3001FH-11P	30.00	33.85
SCT3001FH-12P	33.00	36.85

OPERATION	~ 10	±0.15	DRAW	JUDY	2007.05.09	SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2007.05.09	UNIT	mm		
CHECK	30 ~	±0.50	APPROVE	HELLEN	2007.05.09	SIZE	A4		
APPROVE	Angle	± 2'				SHEET	1/1		
DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	APPROVE		PROJ.	◆	PART NO.	SCT3001FH-XXP
05/12/27	NEW						□	TITLE:	MOLEX3.0 FEMALE HOUSING
								DRAWING NO.	SCT3001