



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 5A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT3001WR-2xXXP
 Poles: 2-12
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions	
	A	B
SCT3001WR-2X1P	---	6.65
SCT3001WR-2X2P	3.00	9.65
SCT3001WR-2X3P	6.00	12.65
SCT3001WR-2X4P	9.00	15.65
SCT3001WR-2X5P	12.00	18.65
SCT3001WR-2X6P	15.00	21.65
SCT3001WR-2X7P	18.00	24.65
SCT3001WR-2X8P	21.00	27.65
SCT3001WR-2X9P	24.00	30.65
SCT3001WR-2X10P	27.00	33.65
SCT3001WR-2X11P	30.00	36.65
SCT3001WR-2X12P	33.00	39.65

OPERATION		~ 10	±0.15	DRAW		JUDY	2007.05.09	SCALE	森康达电子有限公司 SCONBAR ELECTRONIC LIMITED	
DESIGN		20 ~ 30	±0.30	CHECK		MICKY	2007.05.09	UNIT	PART NO.	
CHECK		30 ~	±0.50	APPROVE		HELLEN	2007.05.09	SIZE	SCT3001WR-XXP	
ANGLE		± 2'		APPROVE				SHEET	TITLE:	
DIM		± 2'		APPROVE				PROJ.	DRAWING NO.	
TOL				APPROVE					SCT3001	
MODIFICATION DESCRIPTION				CHANGE						
DATE				APPROVE						
REV		NEW		APPROVE						
0		05/12/27		APPROVE						