


P.C.B. LAYOUT



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 5A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT3001W-S-2xXXP
 Poles: 1-12
 Material: LCP UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions	
	A	B
SCT3001W-S-2x1P	---	6.65
SCT3001W-S-2x2P	3.00	9.65
SCT3001W-S-2x3P	6.00	12.65
SCT3001W-S-2x4P	9.00	15.65
SCT3001W-S-2x5P	12.00	18.65
SCT3001W-S-2x6P	15.00	21.65
SCT3001W-S-2x7P	18.00	24.65
SCT3001W-S-2x8P	21.00	27.65
SCT3001W-S-2x9P	24.00	30.65
SCT3001W-S-2x10P	27.00	33.65
SCT3001W-S-2x11P	30.00	36.65
SCT3001W-S-2x12P	33.00	39.65

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SIMON	SCALE	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW			~ 10 ±0.25 20 ~ 30 ±0.30 30 ~ ±0.50 Angle ± 2° DIM TOL	DESIGN		mm	SCT3001W-S-2xXXP	MOLEX3.0 180C SMT WAFER	SCT3001
						CHECK	MICKY	A4			
						APPROVE	HELLEN	1/1			

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED