



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 5A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER

Part No: SCT3001W-S-E-2xXXP
 Poles: 1-12
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions	
	A	B
SCT3001W-S-E-2x1P	---	6.65
SCT3001W-S-E-2x2P	3.00	9.65
SCT3001W-S-E-2x3P	6.00	12.65
SCT3001W-S-E-2x4P	9.00	15.65
SCT3001W-S-E-2x5P	12.00	18.65
SCT3001W-S-E-2x6P	15.00	21.65
SCT3001W-S-E-2x7P	18.00	24.65
SCT3001W-S-E-2x8P	21.00	27.65
SCT3001W-S-E-2x9P	24.00	30.65
SCT3001W-S-E-2x10P	27.00	33.65
SCT3001W-S-E-2x11P	30.00	36.65
SCT3001W-S-E-2x12P	33.00	39.65

OPERATION	~ 10	±0.25	DRAW	JUDY	2007.05.09	SCALE	6:1	<p>森康达电子有限公司 SCONDAR ELECTRONIC LIMITED</p>
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2007.05.09	UNIT	mm	
CHECK	30 ~	±0.50	APPROVE	HELLEN	2007.05.09	SIZE	A4	
APPROVE	Angle	± 2'	PROJ.			SHEET	1/1	
DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	APPROVE		DRAWING NO.		
05/12/27	NEW							
REV								



森康达电子有限公司
SCONDAR ELECTRONIC LIMITED

SCT3001W-S-E-2xXXP
 MOLEX3.0 180C SMT WAFER

SCT3001