



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 5A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max
WAFER
 Part No: SCT3001WV-XXP
 Poles: 2-12
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions	
	A	B
SCT3001WV-2P	3.00	9.65
SCT3001WV-3P	6.00	12.65
SCT3001WV-4P	9.00	15.65
SCT3001WV-5P	12.00	18.65
SCT3001WV-6P	15.00	21.65
SCT3001WV-7P	18.00	24.65
SCT3001WV-8P	21.00	27.65
SCT3001WV-9P	24.00	30.65
SCT3001WV-10P	27.00	33.65
SCT3001WV-11P	30.00	36.65
SCT3001WV-12P	33.00	39.65

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	JUDY	SCALE	森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
0	05/12/27	NEW			~ 10 ±0.15 20 ~ 30 ±0.30 30 ~ ±0.50 Angle ± 2° DIM TOL.	DESIGN CHECK MICKY 2007.05.09	2007.05.09 HELLEN 2007.05.09	mm	A4	SCT3001WV-XXP
						CHECK		1/1	1/1	MOLEX3.0 180C WAFER
						APPROVE				SCT3001