



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 7A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT3960H-XXP
 Pole: 02-20
 Material: Nylon 66, UL94V-2



PART NO.	Dimensions	
	A	B
SCT3960H-2P	3.96	8.43
SCT3960H-3P	7.92	12.39
SCT3960H-4P	11.88	16.35
SCT3960H-5P	15.84	20.31
SCT3960H-6P	19.80	24.27
SCT3960H-7P	23.76	28.23
SCT3960H-8P	27.72	32.19
SCT3960H-9P	31.68	36.15
SCT3960H-10P	35.64	40.11
SCT3960H-11P	39.60	44.07

PART NO.	Dimensions	
	A	B
SCT3960H-12P	43.56	48.03
SCT3960H-13P	47.52	51.99
SCT3960H-14P	51.48	55.95
SCT3960H-15P	55.44	59.91
SCT3960H-16P	59.40	63.87
SCT3960H-17P	63.36	67.83
SCT3960H-18P	67.32	71.79
SCT3960H-19P	71.28	75.75
SCT3960H-20P	75.24	79.71

OPERATION	~ 10	±0.15	DRAW	CHENA	2005.03.13	SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2005.03.13	UNIT	mm		
ANGLE	30 ~	±0.50	APPROVE	HELLEN	2005.03.13	SIZE	A4	PART NO.	SCT3960H-XXP
DIM	± 2'					SHEET	1/1	TITLE:	MOLEX3.96 HOUSING
DATE			CHANGE			PROU.		DRAWING NO.	SCT3960

REV	0	05/12/27	NEW						
DATE			MODIFICATION DESCRIPTION						