



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 7A AC/DC
 Withstanding Voltage: 1500VAC/minute
 Insulation Resistance: 1000M Ω min.
 Temperature Range: -25°C - +85°C
 Contact Resistance: 20m Ω max

HOUSING
 Part No: SCT3961H-XXP
 Pole: 02-12
 Material: Nylon 66, UL94V-0

PART NO	DIMENSION	
	A	B
SCT3961H-02	3.96	8.20
SCT3961H-03	7.92	12.16
SCT3961H-04	11.88	16.12
SCT3961H-05	15.84	20.08
SCT3961H-06	19.80	24.04
SCT3961H-07	23.76	28.00
SCT3961H-08	27.72	31.96
SCT3961H-09	31.68	35.92
SCT3961H-10	35.64	39.92
SCT3961H-11	39.60	43.88
SCT3961H-12	43.56	47.84

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	CHECK	SCALE	TITLE
0	05/12/27	NEW			~ 10 ± 0.15	DESIGN	MICKY	A4	SCT3961H-XXP
					20 ~ 30 ± 0.30	CHECK	HELLEN	1/1	VH3.96 HOUSING
					30 ~ ± 0.50	APPROVE			SCT3961
					Angle ± 2'				
					DIM TOL				

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED