



PART NO	DIMENSION	
	A	B
SCT3961WR-02	3.96	8.00
SCT3961WR-03	7.92	11.96
SCT3961WR-04	11.88	15.92
SCT3961WR-05	15.84	19.88
SCT3961WR-06	19.80	23.84
SCT3961WR-07	23.76	27.80
SCT3961WR-08	27.72	31.76
SCT3961WR-09	31.68	35.72
SCT3961WR-10	35.64	39.68
SCT3961WR-11	39.60	43.64
SCT3961WR-12	43.56	47.60

SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 7A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT3961WR-XXP
 Pole: 02-12
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

OPERATION	~ 10	±0.15	DRAW	CHENA	2005.03.18	SCALE	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2005.03.18	UNIT	mm
Angle	30 ~	±0.50	APPROVE	HELLEN	2005.03.18	SIZE	A4
DIM	± 2'		PROJ.			SHEET	1/1
DATE	05/12/27		CHANGE			TITLE:	VH3.96 90C WAFER
REV	0		DESCRIPTION	NEW		DRAWING NO.	SCT3961

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

SCT3961WR-XXP