



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 7A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 100MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT3962H-XXP
 Pole: 02-12
 Material: Nylon 66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT3962H-02P	3.96	9.06
SCT3962H-03P	7.92	13.02
SCT3962H-04P	11.88	16.98
SCT3962H-05P	15.84	20.94
SCT3962H-06P	19.80	24.90
SCT3962H-07P	23.76	28.86
SCT3962H-08P	27.72	32.82
SCT3962H-09P	31.68	36.78
SCT3962H-10P	35.64	40.74
SCT3962H-11P	39.60	44.70
SCT3962H-12P	43.56	48.66

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	CHECK	HELEN	2005.03.13	SCALE	UNIT	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW			~ 10 ± 0.15	DESIGN	MICKY	HELLEN	2005.03.13	A4	mm	SCT3962H-XXP	MOLEX5195 HOUSING	SCT3962
					20 ~ 30 ± 0.30	CHECK				1/1				
					30 ~ Angle ± 2'	APPROVE								

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED