



SPECIFICATIONS

Voltage Rating: 600V AC/DC
 Current Rating: 9A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT4201FHA-XXP
 Pole: 2-05
 Material: Nylon 66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT4201FHA-02P	4.20	9.60
SCT4201FHA-03P	8.40	13.80
SCT4201FHA-04P	12.60	18.00
SCT4201FHA-05P	16.80	22.20

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	JUDY	2007.05.09	SCALE	SCT 森康达电子有限公司 SECONDAR ELECTRONIC LIMITED	
0	05/12/27	NEW			~ 10 20 ~ 30 30 ~	DESIGN			mm	A4	SCT4201FHA-XXP
					Angle DIM	CHECK	MICKY	2007.05.09	1/1	TITLE:	MOLEX4.2 FEMALE HOUSING
					± 2'	APPROVE	HELLEN	2007.05.09	PROJ.	DRAWING NO.	SCT4201