



03P

02P, 04P, 05P, 06P

SPECIFICATIONS
 Voltage Rating: 600V AC/DC
 Current Rating: 9A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT4201MH-XXP
 Pole: 2-06
 Material: Nylon 66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT4201MH-02P	4.20	9.60
SCT4201MH-03P	8.40	13.80
SCT4201MH-04P	12.60	18.00
SCT4201MH-05P	16.80	22.20
SCT4201MH-06P	21.00	26.40

OPERATION		~ 10	±0.15	DRAW	YANG	2016.10.27	SCALE	森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
DESIGN		20 ~ 30	±0.30	CHECK	MICKY	2016.10.27	UNIT	PART NO. SCT4201MH-XXP	
CHECK		30 ~	±0.50	APPROVE	ALLEN	2016.10.27	SIZE	MOLEX4.2 MALE HOUSING	
APPROVE		Angle	± 2'	PROJ.			SHEET	DRAWING NO. SCT4201	
TOL.		DM					1/1		

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE
0	05/12/27	NEW		

1	2	3	4	5	6	7	8	9	10
---	---	---	---	---	---	---	---	---	----