



**SPECIFICATIONS**  
 Voltage Rating: 250V AC/DC  
 Current Rating: 7A AC/DC  
 Withstanding Voltage: 1500V AC/minute  
 Insulation Resistance: 100MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**HOUSING**  
 Part No: SCT5082H-XXP  
 Pole: 02-12  
 Material: Nylon 66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT5082H-02P	5.08	10.68
SCT5082H-03P	10.16	15.76
SCT5082H-04P	15.24	20.84
SCT5082H-05P	20.32	25.92
SCT5082H-06P	25.40	31.00
SCT5082H-07P	30.48	36.08
SCT5082H-08P	35.56	41.16
SCT5082H-09P	40.64	46.24
SCT5082H-10P	45.72	51.32
SCT5082H-11P	50.80	56.40
SCT5082H-12P	55.88	61.48

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	CHECK	APPROVE	SCALE	TITLE
0	05/12/27	NEW			~ 10 ± 0.15	DESIGN	MICKY	HELEN	A4	SCT5082H-XXP
					20 ~ 30 ± 0.30	CHECK			1/1	5.08 HOUSING
					30 ~ Angle DIM	APPROVE	HELLEN			SCT5082
					± 2' TOL					

**SCT** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED