


A-A



B-B

**SPECIFICATIONS**  
 Voltage Rating: 250V AC/DC  
 Current Rating: 2A AC/DC  
 Withstanding Voltage: 500V AC/minute  
 Insulation Resistance: 1000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**TERMINAL**  
 Part No: SCT2544T  
 Wire Range: AWG#22-#28 (OD1.6mm)  
 Material: Phos. Bronze  
 Finish: Tin Plated  
 Thickness: 0.2mm  
 Q'TY: 10,000PCS/Reel

REV		DATE		MODIFICATION DESCRIPTION		CHANGE APPROVE		OPERATION		DRAW		CHENA		SCALE		PART NO.		DRAWING NO.	
0		05/12/27		NEW				~ 10 ±0.15		DESIGN		2010.02.11		mm		SCT2544T		SCT2544T	
								20 ~ 30 ±0.30		CHECK		2010.02.11		A4		MX2.54		TERMINIAL	
								30 ~ Angle ± 2'		MICKY		2010.02.11		1/1		SCT2544T			
1								DIM TOL.		HELLEN		PROJ.		DRAWING NO.		SCT2544T			

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED