



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT2544WV-XXPC
 Poles: 2-12
 Material: PBT+GF15%
 Pin: Brass/Gold plated

PART NO.	Dimensions	
	A	B
SCT2544WV-02PC	2.54	7.62
SCT2544WV-03PC	5.08	10.16
SCT2544WV-04PC	7.62	12.70
SCT2544WV-05PC	10.16	15.24
SCT2544WV-06PC	12.70	17.78
SCT2544WV-07PC	15.24	20.32
SCT2544WV-08PC	17.78	22.86
SCT2544WV-09PC	20.32	25.40
SCT2544WV-10PC	22.86	27.94
SCT2544WV-11PC	25.40	30.48
SCT2544WV-12PC	27.94	33.02

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	YANG	SCALE	森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
0	05/12/27	NEW			~ 10 ±0.15	DESIGN		UNIT	A4	PART NO.
					20 ~ 30 ±0.30	CHECK	MICKY	SIZE	1/1	SCT2544WV-XXPC
					30 ~ ±0.50	APPROVE	ALLEN	SHEET		MX2.54 CD-ROM 180C WAFER
					Angle ± 2'			PROJ.		DRAWING NO.
					DIM TOL					SCT2544